

NEMA FRAME MOTORS • SCR RATED

General Specifications:

High voltage permanent magnet DC motors are typically used with an SCR (thyristor) controller in applications requiring adjustable speed and constant torque throughout the speed range. They are also widely used in applications requiring dynamic braking or adjustable speed/reversing capabilities.



Mechanical Features:

Low profile space-saving design. Unique brush holder design provides easy access to brushes and integral constant pressure brush/spring assembly for servicing. Large over-sized brushes assure longer brush life. Heavy-duty, stamped steel, bolt-on base (removable). NEMA C face mounting at no additional cost. Rugged die cast aluminum endshields with cast iron bearing inserts. Permanently lubricated sealed ball bearings. May be converted NEMA 48 base and/or C face using modification kits noted below.

Electrical Features:

Input power of 115 or 230 volts rectified AC when used with an appropriate SCR control. Linear speed/torque characteristics over entire speed range. High starting torque for heavy load applications. Capable of dynamic braking for faster stops. Reversible rotation with simple two-lead connection. For further information on Direct Current Motors, request Bulletin 1600.

PWM RATED PM DC MOTORS

The DC motors listed above have been designed for use on unfiltered SCR (Thyristor) type rectified AC input. These motors may also be used with PWM (pulse width modulated) type DC adjustable speed drives at a higher HP rating. See the chart on page 243 for re-rating data.



MODIFICATION KITS

Motors with S56C or SS56C frame sizes may be converted to 42/48 C face using the following:

Frame	Catalog No.	List Price	Disc. Sym.
SS56C	175182	\$30	A
S56C	175082 ◇	30	A

DC motors in NEMA S56C frame may be converted to 48 base using the following:

Frame	Catalog No.	List Price	Disc. Sym.
S56C	175080 ◇	\$23	A

◇ Addition of base kit will result in non-NEMA BA dimension of 2³/₄". Addition of C face kit will result in conduit box located at 1 o'clock facing lead end.

TEFC • SCR RATED 90 & 180 VOLTS NEMA 56C • C FACE WITH REMOVABLE BASE^Σ

HP	Full Load RPM	NEMA Frame □	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC	"C" Dim. (Inches)
1/4	1750	SS56C	098002	\$412	A	19	90	115	2.5	10.81
	1750	SS56C	098003	412	A	22	180	230	1.4	11.31
1/3	1750	SS56C	098004	437	A	23	90	115	3.5	11.31
	1750	SS56C	098005	437	A	23	180	230	1.7	11.31
	1140	S56C	109098	536	A	32	90	115	3.5	12.81
1/2	2500	SS56C	098006	437	A	22	90	115	5.0	10.81
	2500	SS56C	098007	437	A	22	180	230	2.5	10.81
	1750	SS56C	098000	487	A	26	90	115	5.0	11.81
	1750	S56C	108014	510	A	29	90	115	5.0	12.81
	1750	SS56C	098008	487	A	25	180	230	2.5	11.81
1750	S56C	108015	510	A	30	180	230	2.5	12.81	
11/4	1750	S56C	109099	562	A	40	90	115	5.0	13.81
	2500	SS56C	098009	524	A	26	90	115	7.6	11.81
	2500	S56C	108016	550	A	29	90	115	7.6	12.81
	2500	SS56C	098010	524	A	25	180	230	3.8	11.81
	2500	S56C	108017	550	A	29	180	230	3.8	12.81
17/50	1750	SS56C	098032	591	A	36	90	115	7.6	13.81
	1750	S56C	108018	621	A	38	90	115	7.6	13.81
	1750	SS56C	098069	591	A	36	180	230	3.8	13.81
	1750	S56C	108019	621	A	35	180	230	3.8	13.81
	1140	S56C	109100	760	A	49	90	115	7.5	16.81
1	2500	S56C	108020	591	A	34	90	115	10.0	13.81
	2500	S56C	108021	591	A	38	180	230	5.0	13.81
17/50	1750	S56C	108022	722	A	47	90	115	10.0	16.31
	1750	S56C	108023	722	A	39	180	230	5.0	14.81
	1140	S56C	128023	1440	B	82	90	115	11.0	18.34
1 1/2	2500	S56C	108265	875	A	43	180	230	7.5	14.81
	1750	S56C	108092	903	A	53	180	230	7.6	16.88
	1750	S56/145TC	108262 ■	903	A	54	180	230	7.6	17.38
17/50	145TC		128000	1371	B	70	180	230	7.5	18.34
	2500	S56/145TC	108266 ■	1371	A	51	180	230	8.6	16.88
	1750	145TC	128010	1635	B	83	180	230	9.5	19.34
17/50	182/145TC		128001 ◀	1635	B	84	180	230	9.5	19.34
	3	1750	182/145TC	108502 ◀	1978	B	88	180	14.0	21.75

Σ If base is removed, do not reinstall bolts without using washers to compensate for thickness of base.

◀ NEMA 145TC face mounting with removable NEMA 182T rigid base.

■ NEMA 145TC frame shaft 7/8" x 2 1/4" and NEMA 56 removable base.

□ SS56C motors have a 4.88 inch diameter frame.
S56C motors have a 5.61 inch diameter frame.

TEFC • SCR RATED 90 & 180 VOLTS NEMA 56C • C FACE LESS BASE*

HP	Full Load RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC	"C" Dim. (Inches)
1/4	1750	SS56C	098377	\$400	A	19	90	115	2.5	10.81
1/3	1750	SS56C	098378	425	A	23	90	115	3.5	11.31
1/2	1750	SS56C	098379	475	A	29	90	115	5.0	11.81
3/4	1750	SS56C	098380	579	A	38	90	115	7.6	13.81
1	1750	S56C	109096	710	A	47	90	115	10.0	16.31
	1750	S56C	109097	710	A	39	180	230	5.0	14.81

* No tapped holes provided for attaching a bolt-on base.



DC MOTORS

EXPLOSION-PROOF AND WASHGUARD • SCR RATED

NEMA FRAME • EXPLOSION-PROOF FOR HAZARDOUS LOCATIONS

General Specifications:

These explosion-proof motors are designed and approved for application in hazardous environments having certain explosive gases or materials present.



Features:

Rugged mechanical construction meeting all requirements for safety. UL and CSA listed. NEMA 56C face with removable 56 frame base. Leads exit through 3/4"-14NPT pipe-nipple in the top of the motor frame, opposite the shaft end. **Conduit box is not provided.** See optional conduit box below. These motors have pilot-duty thermostats as standard that must be connected to the SCR control. They are rated for continuous duty with full wave SCR (thyristor) controls. Double-shielded, pre-lubricated ball bearings are standard. Easy brush access for field service. These motor are UL and CSA listed.

Application Notes:

These motors must be applied in accordance with the National Electrical Code, Article #500. For a listing of explosive agents, consult NFPA Publication 497M.

EXPLOSION-PROOF • CLASS I, GROUPS C & D - CLASS II, GROUPS F & G • SCR RATED 90 & 180V C FACE WITH REMOVABLE BASE

HP	Full Load RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC	"C" Dim. (Inches)
1/3	1750	S56C	118015	\$1445	A	27	90	115	3.5	13.41
	1750	S56C	118016	1632	A	30	90	115	4.7	14.41
1/2	1750	S56C	118017	1632	A	32	180	230	2.5	14.41
	1750	S56C	118018	2021	A	40	90	115	7.1	16.41
3/4	1750	S56C	118019	2021	A	36	180	230	3.3	16.41

EXPLOSION-PROOF CONDUIT BOX

UL and CSA listed for Class I, Group C & D, and Class II, Groups F & G locations. Has grounding screw and all hardware provided. Mounts to motor by 3/4"-14NPT opening at rear of box. For NEMA 56 frame motors only.



Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)
175026	\$58	A	2

NEMA FRAME • WASHGUARD

LEESON WASHGUARD

motors are designed for extended life in applications requiring regular washdown as in food processing, or otherwise wet, high humidity environments. WASHGUARD motors retard the entrance of water during cleaning operations and release any water that does enter the motor. Extra protection for the motor's interior prevents rust and corrosion build-up and drains release trapped moisture to insure a longer life than possible with a standard motor.



Mechanical Protection Features:

High quality, corrosion resistant 303 stainless steel shaft plus lubricated spring-loaded contact seals and patented, "V" ring Forsheda seal deflect water, protect bearings and the motor's interior. Double sealed, oversized bearings with high temperature moisture resistant lubricant are used.

Frame, base, endshields, armature and interior components protected by enamel and polyester compounds of outstanding adhesion and resistance to moisture, acids, alkalis and oil.

Cast conduit box with threaded entrance, drain holes and tough, high temperature Nitrile gaskets keep water out and resist deflection under high pressure washdowns Conduit box cover and fan cover, when used, are type 304 stainless steel.

Four drains in each endshield at 3,6,9, and 12 o'clock purge water, and can be repositioned for maximum effectiveness regardless of the motor's mounting. Machined fits are sealed, and nylon gaskets are used to seal bolt heads. Stainless steel data plate.

Chemically inert static free fan is positively positioned on the shaft by opposing flats, shoulder and snap ring arrangement and protected by heavy gauge, stainless steel fan guards. Finished in USDA approved tough white epoxy for superior corrosion resistance and protection against harsh caustic cleaning solutions.

WASHGUARD • NEMA C FACE • REMOVABLE BASE TENV • SCR RATED 90 & 180 VOLTS

HP	Full Load RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC	"C" Dim. (Inches)
1/4	1750	S56C	108423	\$534	A	23	90	115	2.7	10.69
	1750	SS56C	098375	534	A	21	180	230	1.4	10.22
1/3	1750	S56C	108424	564	A	26	90	115	3.5	11.69
	1750	SS56C	098376	564	A	22	180	230	1.7	10.22
1/2	1750	S56C	108226	632	A	38	90	115	4.9	13.69
	1750	S56C	108227	632	A	43	180	230	2.4	13.69
3/4	1750	S56C	108228	766	A	53	90	115	7.0	15.69
	1750	S56C	108229	766	A	50	180	230	3.5	15.69
1	1750	S56C	108230**	936	A	45	90	115	10.0	15.81
	1750	S56C	108231**	936	A	42	180	230	5.0	14.81
1 1/2	1750	S56C	108232**	1194	A	50	180	230	7.6	16.81

WASHGUARD • IEC FRAME • TENV IP55 B5 FLANGE WITH REMOVABLE B3 BASE[Ⓡ] ▲ SCR RATED 180 VOLTS

Rated HP	Output kW	Full Load RPM	IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	F.L. Amps DC	"C" Dim. (Inches)
1/2	.37	1750	71	098040	\$560	A	22	180	2.5	10.69
3/4	.55	1750	80	108407	758	A	52	180	3.5	16.02

** These motors are totally enclosed fan cooled.

Ⓡ If base is removed, do not reinstall bolts without using washers to compensate for the thickness of base.

▲ These WASHGUARD motors are modular design but stocked with B5 flange and B3 foot. The foot is removable. The B5 flange can be replaced with a B14 face or other diameter B5 flanges noted on page 85.

Catalog numbers in blue are NEW items.

SUB-FHP MOTORS

General Specifications:

Precision subfractional horsepower DC permanent magnet motors designed for use with full wave non-filtered SCR controls for adjustable speed applications requiring dynamic braking and constant torque throughout the speed range.



31/34 Frame

Mechanical Features:

Compact space saving designs. Ball bearings. Long-life brushes for demanding applications. Brushes easily replaced without disassembly of the motor. Standard mounted conduit box on 31 and 34 frame models simplifies connections.



25 Frame

Electrical Features:

Continuous duty with full wave un-filtered rectified SCR (thyristor) controls. Linear speed torque characteristics throughout the speed range. High starting torques. Reversible rotation from a simple two lead connection.

SUB-FHP IP55 WASHGUARD MOTORS

General Specifications:

Precision subfractional horsepower DC permanent magnet motors. Designed for use with fullwave non-filtered SCR controls or battery supplied low voltage for adjustable speed applications requiring constant torque throughout the speed range.



Mechanical Features:

Corrosion resistant 303 stainless steel. shaft with spring-loaded contact shaft seal protect the double sealed ball bearings and motor interior.

Frame, endshields, armature and interior components protected by enamel and polyester compounds for resistance to moisture, acids, alkalies and oil.

Cast conduit box with threaded conduit holes and Nitrile gaskets keep water out. The conduit box cover is made from 304 stainless steel.

For any condensation that may accumulate inside the motor a one-way stainless steel vapor vent is provided. All hardware is stainless steel. Motor painted with white epoxy for superior corrosion resistance and protection. Machined fits between the endbells and motor frame and sealed with gaskets. Thru-bolt heads and nuts sealed with fiber washers. O-rings under each threaded brush cover.

Application Notes:

LEESON WASHGUARD motors are designed for extended life in applications requiring regular washdown or otherwise wet environments. Washguard motors retard the entrance of water. Extra protection for the motor's interior prevents rust and corrosion build-up and releases trapped moisture to insure a longer life than possible with a standard motor.

Dimensions:

Found on page 291.

SCR RATED (90 & 180 V) • TENV • SQUARE FLANGE OR C FACE

HP	Full Load RPM	Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC
1/25	3500	25AS	M1110014 [ⓑ]	\$190	S	3	90	115	0.5
	1750	25CS	M1110003 [ⓑ]	196	S	3	90	115	0.5
1/15	3500	25CS	M1110015	203	S	2	90	115	0.7
	1750	31BS	M1120013 [ⓑ]	210	S	5	90	115	0.8
	1750	31BS	M1120039	210	S	7	180	230	0.4
1/10	3500	31BS	M1120060	210	S	5	90	115	1.3
	1750	31CS	M1120014	249	S	7	90	115	1.1
	1750	31CS	M1120041	249	S	7	180	230	0.6
1/8	3500	31CS	M1120059	249	S	6	90	115	1.5
	1750	31ES	M1120027	270	S	7	90	115	1.3
	1750	31ES	M1120045	270	S	7	180	230	0.7
	1750	34D42CZ	M1130053	280	S	8	90	115	1.4
	1750	34D42CZ	M1130118	280	S	7	180	230	0.7
1/6	3500	31ES	M1120058	270	S	9	90	115	1.9
	1750	31GS	M1120042	273	S	9	90	115	1.8
	1750	31GS	M1120043	273	S	11	180	230	0.9
	1750	34E56C	M1130054	286	S	11	90	115	1.7
	1750	34E56C	M1130119	286	S	11	180	230	0.9
1/4	3500	31GS	M1120062	285	S	9	90	115	2.6
	1750	34G56C	M1130055**	295	S	13	90	115	2.7
	1750	34G56C	M1130120**	295	S	13	180	230	1.3

[ⓑ] 25 frame motors have provisions for an optional conduit box catalog number M1760000, see page 150.
** These motors are totally enclosed fan cooled.

SCR RATED (90 V) • TENV • SQUARE FLANGE OR C FACE

HP	Full Load RPM	Frame	Catalog Number	List Price	Disc. Sym.	Arm. Volts DC	Control Volts AC Input	F.L. Amps DC
1/8	1750	31S	M1120181	\$340	S	90	115	1.5
1/6	1750	31S	M1120183	345	S	90	115	1.9
1/4	2500	32F42CZ	M1120185	375	S	90	115	1.9

LOW VOLTAGE (12 V) • TENV SQUARE FLANGE OR C FACE

HP	Full Load RPM	Frame	Catalog Number	List Price	Disc. Sym.	Arm. Volts DC	F.L. Amps DC
1/8	1750	31S	M1120182	\$355	S	12	10.5
1/6	1750	31S	M1120184	360	S	12	14.5
1/4	2500	32F42CZ	M1120186	390	S	112	20

Catalog numbers in blue are NEW items.



DC MOTORS

METRIC (IEC) FRAME • SCR RATED

DC METRIC (IEC) FRAME MOTORS IP54

General Specifications:

These metric dimensioned motors are built to IEC 34-1 electrical and mechanical standards.

The IEC 63 and smaller frames are stocked with an integral B5 flange or B14 face less base. An optional B3 rigid base kit is available.

A unique modular approach for IEC 71 frame and larger allows the motor to be field modified to B3 rigid base mounted construction, B5 flange mounted or B14 face mounted construction using conversion kits. Please note that one or more of the mounting kits must be used with IEC motors of these frame sizes. See listing on next page for B5 flange and B14 face kits. B3 rigid base kits are listed below.

Electrical & Mechanical Features:

A terminal board is provided for connections. All fasteners are metric. Electrical and mechanical features are the same as listed for the NEMA frame motors on the opposite page. Tachometer mounting kits are available—please contact LEESON for data.



B5 IEC 56 & 63



B14 IEC 56 & 63



B3 FOOT MOUNTING KITS

(For DC Metric Motors Only)

All motors are stocked with provisions to accommodate B3 foot mountings with the packages noted below.

IEC Frame	Catalog Number	List Price	Disc. Sym.
56	175142	\$15	A
63	175143	15	A
71	175144	22	A
80	175145	22	A
90	175146	28	A

TOTALLY ENCLOSED • SCR RATED 180 VOLTS⚡ WITH B5 FLANGE

KW/HP	Full Load RPM	IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	F.L. Amps DC	"C" Dim. Inches (mm)
0.06/1/12	1800	56	M1130146●	\$303	S	8	0.5	6.24 (158.6)
0.09/1/8	3000	56	M1130150●	303	S	9	0.7	6.74 (171.3)
	1800	56	M1130147●	326	S	10	0.7	7.55 (191.7)
0.12/1/6	3000	56	M1130151●	315	S	9	0.9	7.55 (191.7)
	1800	63	M1130148	371	S	7	0.9	8.30 (210.8)
0.18/1/4	3000	63	M1130152●	342	S	11	1.3	8.78 (223.1)
	1800	63	M1130149	398	S	13	1.3	9.50 (241.3)
0.25/1/3	3000	63	M1130153	379	S	11	1.7	9.50 (241.3)

These motors have accommodations for B3 base mountings with the kits below.

TOTALLY ENCLOSED • SCR RATED 180 VOLTS⚡ WITH B14 FACE

KW/HP	Full Load RPM	IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	F.L. Amps DC	"C" Dim. Inches (mm)
0.06/1/12	3000	56	M1110024●	\$271	S	6	0.4	6.34 (177.0)
	1800	56	M1130136●	303	S	8	0.5	6.24 (158.6)
0.09/1/8	3000	56	M1130140●	303	S	9	0.7	6.74 (171.3)
	1800	56	M1130137●	326	S	14	0.7	7.55 (191.7)
0.12/1/6	3000	56	M1130141●	315	S	10	0.9	7.55 (191.7)
	1800	63	M1130138	371	S	8	0.9	8.30 (210.8)
0.18/1/4	3000	63	M1130142●	342	S	10	1.3	8.78 (223.1)
	1800	63	M1130139	398	S	10	1.3	9.50 (241.3)
0.25/1/3	3000	63	M1130143	379	S	10	1.7	9.50 (241.3)

Except for M1110024, these motors have accommodations for B3 base mountings with the kits below.

TEFC • SCR RATED 180 VOLTS⚡ • ROUND BODY


KW/HP	Full Load RPM	IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	F.L. Amps DC	"C" Dim. Inches (mm)
0.25/1/3	1800	71	098014	\$386	A	23	1.7	11.28 (286.5)
0.37/1/2	3000	71	098016	413	A	21	2.5	10.78 (273.8)
	1800	71	098015	439	A	26	2.5	11.78 (299.2)
0.55/3/4	3000	71	098017	476	A	24	3.6	11.78 (299.2)
	1800	80	108369	543	A	34	3.5	14.64 (371.9)
0.75/1	3000	80	108372	543	A	45	4.9	14.64 (371.9)
	1800	80	108370	671	A	48	4.6	17.14 (435.4)
1.1/1 1/2	3000	80	108373	601	A	47	7.1	16.14 (410.0)
	1800	80	108371	886	A	52	7.0	17.14 (435.4)
	1800	90L	118007	1319	B	64	7.5	18.97 (481.8)
1.5/2	3000	90L	118009	1319	B	72	10.0	18.47 (469.1)
	1800	90L	118008	1582	B	84	9.5	20.47 (519.9)
2.2/3	3000	90L	118010	1582	B	82	16.0	19.47 (494.5)
	1800	112M	118014	2009	B	90	14.0	21.79 (553.5)

IMPORTANT: These round body motors require either a B3 rigid base, B14 face or B5 flange kit. Catalog number 118014 comes complete with IEC 112 B14 face and B3 foot; shaft diameter is 24mm.

- ⚡ For 230 VAC input controls.
- These motors are totally enclosed, non-ventilated. Other ratings utilize IC41 cooling—external cooling fan on motor shaft.

FLANGE AND FACE KITS FOR DC METRIC (IEC) FRAME MOTORS

An advantage of LEESON'S modular design concept is the possible use of a different diameter B5 flange or B14 face than is normally assigned to a motor by IEC dimensional standards. This flexibility makes it possible to accommodate a wide variety of gear reducers, pumps and similar close coupled motor mounted loads.



Round body DC Metric IEC motors will accept any of the flange or face kits listed.


B5 FLANGE KITS (For DC Metric Motors Only)

IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	BD Flange Dia. (mm)	AK Register (mm)	BF Hole (mm)	AJ Bolt Circle (mm)
71	175106	\$46	A	2	160	110	9	130
80	175108	46	A	3	200	130	12	165
90S/90L	175108	46	A	3	200	130	12	165
100L/112M	175137	114	A	5	250	180	15	215

B14 FACE KITS (For DC Metric Motors Only)

IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	BD Flange Dia. (mm)	AK Register (mm)	BF Tap (mm)	AJ Bolt Circle (mm)
71	175107	\$46	A	1	105	70	6	85
80	175109	46	A	1	120	80	6	100
90S/90L	175129	46	A	1	140	95	6	115
100L/112M	175130	114	A	2	160	110	6	130

CONDENSED DIMENSIONS • DC METRIC (IEC) FRAME MOTORS



*For overall length, see motor listing.

IEC FRAME DIMENSIONS (Millimeters)

IEC Frame	Mounting					Shaft					B14 Face/B5 Flange					General								
	2E	2F	BA	D	H	U	AH	KEY	S	R	TAP	AJ	AK	BD	BF	BB	AB	XP	B	O				
56	90	71	36	56	6	9	20	15	3	7.0	M3	65	100	50	80	120	M5	7	2.5	2.5	83	96	90	99
63	100	80	40	63	7	11	23	19	4	9.0	M4	75	115	60	95	90	M5	9	2.5	3.0	116	96	96	108
71	112	90	45	71	7	14	30	26	5	11.5	M5	85	130	70	110	105	M6	9	2.5	3.5	114	130	105	132
80	125	100	50	80	10	19	40	33	6	16.0	M6	100	165	80	130	120	M6	12	3.0	3.5	124	149	127	151
90S	140	100	56	90	10	24	50	36	8	20.5	M8	115	165	95	130	140	M8	12	3.0	3.5	135	182	152	173
90L	140	125	56	90	10	24	50	36	8	20.5	M8	115	165	95	130	140	M8	12	3.0	3.5	135	182	152	173
100L	160	140	63	100	12	28	60	41	8	24.5	M10	130	215	110	180	160	M8	15	3.5	4.0	135	182	176	173
112M	190	140	70	112	12	28	60	41	8	24.5	M10	130	215	110	180	160	M8	15	3.5	4.0	162	231	176	225

◇ Without face or flange AH shaft dimension is 12mm longer.

All dimensions in millimeters (1 inch = 25.4mm)



DC MOTORS

NEMA FRAME • LOW VOLTAGE 12 & 24 VOLTS

NEMA FRAME LOW VOLTAGE MOTORS

General Specifications:

Low voltage permanent magnet DC motors are suitable for installations having battery or solar powered operations, or generator supplied low voltage DC.

Mechanical Features:

Unique brush holder design provides easy access to brushes and integral, constant pressure brush/spring assembly for servicing. Larger over-sized brushes assure longer brush life. Heavy-duty, stamped steel, bolt-on base (removable). NEMA C face mounting flange at no additional cost. High strength rolled steel frame. Rugged die cast aluminum endshields with steel bearing inserts. Permanently lubricated sealed ball bearings. May be converted to NEMA 48 frame base dimensions or NEMA 42/48 frame C face dimensions using modification kits noted on page 79.

Electrical Features:

High starting torques for heavy load applications. Linear speed/torque characteristics over entire speed range. Capable of dynamic braking for faster stops. Reversible rotation and simple two-lead connection. Convenient wiring access.



DC METRIC (IEC) FRAME MOTORS IP54

General Specifications:

These metric dimensioned motors are built to IEC 34-1 electrical and mechanical standards.

The IEC 63 and smaller frames are stocked with an integral B5 flange or B14 face less base. An optional B3 rigid base kit is available.

A unique modular approach for IEC 71 frame and larger allows the motor to be field modified to B3 rigid base mounted construction, B5 flange mounted or B14 face mounted construction using conversion kits. Please note that one or more of the mounting kits must be used with IEC motors of these frame sizes. See listing on page 83 for B5 flange and B14 face kits. B3 rigid base kits are listed below.

Electrical & Mechanical Features:

A terminal board is provided for connections. All fasteners are metric. Electrical and mechanical features are the same as listed for the NEMA frame motors on the opposite page. Tachometer mounting kits are available—please contact LEESON for data.



B5 IEC 56 & 63

B14 IEC 56 & 63

71 & 80 IEC with Modular Flange & Base Kits

LOW VOLTAGE (12 & 24V) • TENV/TEFC NEMA C FACE WITH REMOVABLE BASE^Σ

HP	Full Load RPM	NEMA Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Arm. Volts DC	F.L. Amps DC	"C" Dim. (Inches)
1/4	1800	S56C	108045♣	\$443	A	21	12	21.0	10.44
1/3	1800	S56C	108046♣	488	A	24	12	27.0	11.44
	1800	S56C	108050♣	466	A	22	24	13.5	10.94
1/2	1800	S56C	108047♣	506	A	29	12	39.0	12.44
	1800	S56C	108051♣	484	A	29	24	20.0	11.94
	1800	SS56C	098381	460	A	29	36	13.5	10.81
	1800	SS56C	098382	445	A	29	48	11.0	10.81
3/4	1800	S56C	108048♦	560	A	30	12	58.0	13.81
	1800	S56C	108052	505	A	30	24	29.0	12.81
1	1800	S56C	108322♦	666	A	39	12	80.0	13.81
	1800	S56C	108053♦	614	A	37	24	39.0	13.81
	1800	S56C	109101	587	A	37	36	25.5	13.81
	1800	S56C	109102	567	A	37	48	18.5	13.81
1 1/2	1800	S56CZ	109103♦□	895	A	39	24	60.0	17.38
	1800	S56CZ	109104♦□	884	A	37	36	36.0	16.82
	1800	S56CZ	109105♦□	853	A	37	48	27.0	16.82
2	1800	S56CZ	109106♦□	1121	A	42	24	70.0	16.31
	1800	S56CZ	109107♦□	1037	A	42	36	49.0	16.31
	1800	S56CZ	109108♦□	997	A	42	48	38.0	16.31

- ♣ Built-in conduit box located at 12:00.
- ♦ Studs at 12:00.
- Σ If base is removed, do not reinstall bolts without using washers to compensate for thickness of base.
- S56CZ motors have mounting bases with NEMA 56 mounting holes, NEMA 56/143-5T C-face and a NEMA 143-5T shaft extension (7/8" dia. x 2 1/4" long).
- These motors are totally enclosed, non-ventilated.
- SS56C motors have a 4.88 inch diameter frame.
- S56C motors have a 5.61 inch diameter frame.

METRIC (IEC) FRAME • LOW VOLTAGE (24V) • TEFC/TENV • MODULAR DESIGN

kW/HP	Full Load RPM	IEC Frame	Catalog Number	List Price	App. Wgt. (lbs.)	F.L. Amps DC	C Dim. (inches)
0.06/1/2	3000	56	M1110025^●	\$240	5	3.3	5.34
	1800	56	M1110026^●	273	6	3.4	6.34
0.18/1/4	3000	63	M1130206*	307	13	11.0	7.75
	3000	63	M1130296^	307	9	11.0	7.75
	1800	63	M1130207*	352	13	10.0	8.75
	1800	63	M1130297^	352	9	10.0	8.75
0.37/1/2	3000	71	098065	421	19	11.0	10.77
		71	098066	436	23	20.0	11.27
	1800	71	098067	460	23	20.0	12.27
0.75/1	3000	80	108456♦	504	33	40.0	14.14
	1800	80	108455♦	591	52	39.0	14.64
1.1/1 1/2	3000	80	108457♦	562	33	65.0	15.64
1.5/2	3000	80	108458♦	646	43	78.0	17.14

IMPORTANT: IEC 71 and 80 frame motors in this chart are round body and require either B14 face, B5 flange or B3 foot from kits shown on pages 82-83.

- * Dedicated B5 Flange
- ^ Dedicated B14 Face
- These motors are totally enclosed, non-ventilated. Others are TEFC/IC41 cooling – external cooling fan on motor shaft.

Catalog numbers in blue are NEW items.

SUB-FHP LOW VOLTAGE MOTORS

General Specifications:

Precision sub-fractional horsepower low voltage direct current permanent magnet motors designed for battery or solar powered operations, or generator supplied low voltage DC.



Mechanical Features:

Compact space saving designs. Standard conduit box simplifies connections. Ball bearings. Long-life brushes for demanding applications. Brushes easily replaced without disassembly of motor.

Electrical Features:

High starting torques for heavy load applications. Linear speed/torque characteristics over entire speed range. Capable of dynamic braking for faster stops. Reversible rotation from a simple two lead connection. Class F insulated with high temperature welded commutators.

LOW VOLTAGE (12 & 24V) • TENV • SQUARE FLANGE

HP▲	Full Load RPM	Frame	Catalog Number	List Price	Disc. Sym.	App. Wgt. (lbs.)	Input Volts DC	F.L. Amps DC
1/20	1750	25CS	M1110006*	\$180	S	3	12	4.4
1/10	4200						24	4.4
1/14	1750	31AS	M1120040	210	S	4	12	7.7
1/7	4200						24	7.7
1/7	1750	31ES	M1120044	279	S	9	12	13.0
1/4	3500						24	13.0
1/6	1800	31GS	M1120046	294	S	8	12	14.0
1/3	3900						24	14.0

* 25 frame motors have provision for an optional conduit box catalog number M1760000, see page 156.

For dimensions, see drawings on page 291.

▲ These motors may be operated at 12, 24V, or at intermediate voltages between 12 and 24V, within horsepower ranges noted.

TACHOMETER MOUNTING KITS FOR DC MOTORS

All necessary parts to mount listed tachometers to stock TEFC SCR motors. Consists of machined cast fan cover, coupling and hardware. Does not include tachometer. Tach adapter kit is not suitable for catalog number 108502.



Tachometer Type	NEMA Frame	IEC Frame	Catalog Number	List Price	Disc. Sym.	App. Wt. (lbs.)
GE 5PY Series	SS56	71	175156	\$175	A	5
	S56	80	175193	183	A	5
	56/145	—	175158	359	A	5
Servo-tek SA740 Series	SS56	71	175157	184	A	8
	S56	80	175194	194	A	8
	56/145	—	175159	410	A	8

LOW VOLTAGE ADJUSTABLE SPEED CONTROLLERS

LEESON's DC to DC controllers are a chassis type design, that accept a DC input voltage and output a DC power voltage to control the motor speed. The speed may be varied with the potentiometer that is shipped loose with the control or an external voltage signal.



Higher design efficiency results in longer running time between battery charges than is possible with traditional methods of speed control using resistance in series with the battery.

Typical Operating Features: Provides smooth 40 to 1 speed range capability for mobile equipment. Maintains variable speed control as batteries discharge. Adjustable min/max speed, IR compensation, and 200 % current limit overload protection. Inhibit pin terminals provide customer optional start-stop without breaking battery lines. Green LED power on indicator is provided.

Catalog number 175290 does not require a heat sink, and measures 6.9L x 4.44W x 2.19D. Catalog numbers 175291 & 175292 do require heat sink, which is included and measures 7.78L x 6.9W x 3.25D.

Input Voltage	Max. Amp Ratings	Catalog Number	List Price	App. Wgt.(lbs.)	Disc. Sym.
12/24	16	175290	\$344	2	A
12/24	60	175291	420	4	A
36/48	60	175292	420	4	A

COMMERCIAL DUTY METRIC (IEC) FRAME MOTORS

Specially designed low voltage DC motors for use in OEM applications. Combination of features and low cost makes these motors excellent for many uses. All feature IP44 (TENV) enclosure and dedicated B14 face mount. Rated S1 for continuous duty, and zinc plated steel frame construction.



12, 24V & 90 VOLT • TENV B14 FACE MOUNT

HP	Full Load RPM	IEC Frame▲	Catalog Number	List Price▲	App. Wgt. (lbs.)	Arm. Volts DC	F.L. Amps DC
1/15	3000	56	980.159	\$125	2,3	12	6,0
	3000	56	980.143	125	2,3	24	3,2
	3000	56	980.549	120	2,3	90	.8
1/8	3000	56	970.600	145	3,0	12	12,0
	3000	56	970.601	145	3,0	24	5,30
	3000	56	970.576	140	3,0	90	1.6
1/6	3000	56	970.620	155	3,5	12	13,0
	3000	56	970.621	155	3,5	24	6,50
	3000	56	970.577	150	3,5	90	1.9

For dimensions, see drawings on page 291.

▲ Use "S" Discount Symbol.

Catalog numbers in blue are NEW items.